Technical Data Sheet



OWS Über Power Brake Fluid DOT 4

100% Fully Synthetic Brake Fluid DOT 4

OWS Über Power Brake Fluid DOT 4 is a 100% fully synthetic high-performance brake fluid with an elevated dry boiling point of 250°C and a wet boiling point of 168°C. Enhanced corrosion protection for all hydraulic brake systems.

OWS Über Power Brake Fluid DOT 4 is for use in hydraulic clutch systems, according to manufacturer's instructions.

OWS Über Power Brake Fluid DOT 4 fulfils or exceeds the following specifications: US FMVSS 116 DOT 4 / DOT 3 SAE J 1704 / J 1703 ISO 4925

Test	Method	Unit	Result
Density @20°C	DIN 51 757	kg / L	1.04
Kinematic Viscosity @-40°C	DIN EN ISO 3104	cSt	1200
Kinematic Viscosity @100°C	DIN EN ISO 3104	cSt	2.17
Dry Boiling Point	FMVSS 116	С	250
Wet Boiling Point	FMVSS 116	°C	168

Typical properties are typical of those obtained with normal production tolerance and do no constitute a specification.

All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.

OWS Our Workshop System Im Strang 1, 34479 Breuna, Germany Tel : +49 (0) 5693 991 5400 Fax : +49 (0) 5693 991 5409 www.ows-germany.com Email: info@ows-germany.com