

OWS Multi Edge SAE 15W-40

Advanced Multi-Grade Fuel Economy SHPD Oil for Mixed Fleet Applications

OWS Multi Edge SAE 15W-40 is a high-quality modern multi-grade motor oil that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Überclean® additive technology reduces carbon and sludge build up even under demanding driving conditions.

OWS Multi Edge SAE 15W-40 is manufactured using the highest quality base stocks and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS Multi Edge SAE 15W-40 is designed for mixed fleet applications, from passenger cars to commercial vehicles. It provides optimum protection against corrosive wear, foaming and viscosity loss due to shear, valve train wear and oxidative thickening.

OWS Multi Edge SAE 15W-40 fulfills or exceeds the following specifications:

ACEAA3 / B3 / B4 / E7	Allison C-4
API SL/CI-4	Global DHD-1
Renault RLD-2	CAT ECF-1-a / ECF-2
MB 228.3 / 229.1	Cummins CES 20071/-72/-75/-76/-77/-78
MTU Type 2	Deutz DQC III-05
MAN 3275	JASO DH-1
Volvo VDS-3	
Mack EO-M PLUS	

Test	Method	Unit	Result
Density @15°C	ASTM D4052	kg / L	0.867
Kinematic Viscosity @40°C	ASTM D445	cSt	90.8
Kinematic Viscosity @100°C	ASTM D445	cSt	13.4
Viscosity Index	ASTM D2270		150
Flash Point, COC	ASTM D92-05A	°C	> 225
Pour Point	ASTM D97	°C	-39

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.