

OWS Truck HC Pro SAE 10W-40

Fully HC-Synthetic Engine Oil for Truck Engines with extended oil drain intervals

OWS Truck HC Pro SAE 10W-40 is a fully HC-Synthetic based Ultra High Performance Diesel (UHPD) Motor Oil that protects against friction, heat and corrosion, keeping engines healthy and efficient.

OWS Überclean® additive technology reduces carbon or sludge build up even under severe driving conditions. Its special additive formulation provides significantly low friction with strengthened oil film for greater engine response and fuel efficiency.

OWS Truck HC Pro SAE 10W-40 is manufactured using the highest quality HC-Synthetic base stocks and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS Truck HC Pro SAE 10W-40 fulfills or exceeds the following specifications:

ACEA E6 / E7	Cummins CES 20071 / 72 / 76 / 77 / 78
API CJ-4	MACK EO-M Plus
Global DHD-1	DEUTZ DQC III-10
CAT ECF-1-a / ECF-2	MAN 3277
MB 228.5	Detroit Diesel 93K215
MTU Type 3	Volvo VDS-3
Renault RXD / RLD-2	

Test	Method	Unit	Result
Density @15°C	ASTM D4052	kg / L	0.865
Kinematic Viscosity @40°C	ASTM D445	cSt	95
Kinematic Viscosity @100°C	ASTM D445	cSt	14.4
Viscosity Index	ASTM D2270		158
Flash Point, COC	ASTM D92-05A	°C	> 220
Pour Point	ASTM D97	°C	< -35

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.

All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.