

## OWS Truck King LA SAE 5W-30

*High Performance Low Ash Ultra High Performance Diesel (UHPD) Engine Oil*

OWS Truck King LA SAE 5W-30 is a fully synthetic PAO based Ultra High Performance Diesel (UHPD) formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Überclean® additive technology reduces carbon or sludge build up even under severe driving conditions.

OWS Truck King LA SAE 5W-30 is manufactured using the highest quality Fully Synthetic base stocks and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS Truck King LA SAE 5W-30 is designed for use in modern commercial and mixed fleet vehicles equipped with the latest exhaust after treatment technology.

OWS Truck King LA SAE 5W-30 fulfills or exceeds the following specifications:

API CI-4  
ACEA E6 / E7 / E9  
MAN M 3677 / M 3477  
MB 228.51  
Volvo VDS-4  
Scania Low Ash  
Renault RVI RXD  
FTP Iveco  
DAF GP-2  
MACK EO-M+

Test	Method	Unit	Result
Density @15°C	ASTM D4052	kg / L	0.855
Kinematic Viscosity @40°C	ASTM D445	cSt	67.8
Kinematic Viscosity @100°C	ASTM D445	cSt	11.5
Viscosity Index	ASTM D2270		165
Flash Point, COC	ASTM D92-05A	°C	> 220
Pour Point	ASTM D97	°C	< -40

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.

All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.